

Steps for update sd c4 firmware to V2.30

1. Prepare 6 ordinary AA NO. 5 battery, do as "1,steps-for-installing-battery.pdf" to install the battery

(The battery should be new, full with power, or the firmware update will be failed). Then use the green lan cable to connect the computer and the mb sd c4 main unit.

OBD cable connect the SDC4 main unit and the vehicle

(If cannot connect with the vehicle, you can use OBD 12V power to replace)

2. Open 2012.09 DAS software, go to C:\programm files\SDconnect

Toolkit file, check if there are three files as below:

Update_automatic, Update_manual;Update_Special.

Just as the following pic, if the file names are wrong pls correct them.



名称	大小	类型	修改日期
bin		文件夹	2012-10-12 16:20
doc		文件夹	2012-10-12 16:20
SelfTest		文件夹	2012-10-12 16:20
update_automatic		文件夹	2012-10-12 16:20
update_manual		文件夹	2012-10-12 16:20
update_special		文件夹	2012-10-12 16:20
TK2.reg	2 KB	注册表项	2012-7-30 7:33
TK2_Delete_Files.bat	1 KB	MS-DOS 批处理文件	2012-7-30 7:35
Toolkit_list.bat	1 KB	MS-DOS 批处理文件	2009-8-6 11:48

4. Restart your computer

5. You can begin to update the file. check file: "2,Update SDconnect.pdf"